



### Rail

Minimum Staircase Width	750 mm
Rail to Wall Distance (Incl. Rail)	160 mm min.
Material of Rail	Steel
Diameter of Tube (Upper/Lower)	56mm / 40mm
Maximum Rail Length	40 m
Min. Space for Rail Start	340 mm
Rail Fixing	On every 3rd and 5th Stair
Wall Fixing	optional
Radius of Curve (Depends on Incline) / 180 ° (Outside)	0°      200 mm
	15°      180 mm
	30°      147 mm
	50°      95 mm
Maximum Incline	< 75 Grad°
Driving Speed	10 cm / sek.
Lifting Capacity	125 kg - 150 kg

### Chair

Swivel Seat	yes / powered
Stand- Perch Seat	optional
Dimensions of Chair	
Seat Height Bottom / Foot Rest	565 mm / 60 mm
Seat Height	505 mm
Folded Out	640 mm
Folded Up	380 mm
Seat Measured to Front of Backrest	410 mm

### Control

Joystick	Standard
2 Button Switch	optional
Keyswitch (To Prevent Unauthorized Use)	optional
Remote Control (2 PCs.) (868 MHz)	ja

### Engine / Drive:

Enginepower	340 Watt
Power Supply 230 V , 50 Hz	Socket Upstairs / Downstairs
Battery	Yes / 24 V
Drive	Gear Rack



# HAWLE TREPPENLIFTE

Member of HAWLE GROUP INTERNATIONAL